



WORLDWIDE MOTOR CONTROLS
Soft Starters
General Purpose Solid State Soft Starters

MODEL: WWPICSSRV12-600



General Product Specifications

- NEMA 4 Enclosure
- Service entrance rated
- Advanced Motor Protection
- Full panel surge protection
- Integral full rated bypass contactor with X-Line mode
- Front panel indicators and keypad
- Start/stop, HOA, reset buttons
- Current imbalance, overcurrent, undercurrent, phase loss, shorted load, and ground fault protections standard
- Soft stop feature eliminates water hammer
- Run pilot light
- Emergency stop push button
- Illuminated fault/reset push button

| | | |
|----------------------|---|---|
| Rated Power | 230V | 300 HP |
| | 460V | 600 HP |
| Max Full Load Amps | | 800 A |
| Outside Dimensions | | 92x36x30 |
| Input Voltage | 208-480VAC \pm 10%, 50/60Hz Optional 380, 415, 575VAC | |
| Overload Rating | 500% for 30s | |
| Overload Range | 560-840 A | |
| CT Rating | 700:5 | |
| Ambient Conditions | 0° to 40 °C, 5-95% relative humidity, 0-3300ft above sea level (Can be designed to operate outside these conditions) | |
| Inputs | 7 | dry contacts using 120VAC |
| Programmable Outputs | 3 | 2-Form C (5A, 240VAC max) 1- Form A 26 programmable functions |



DRIVING & Controlling

WorldWideElectric

Industry

