

WORLDWIDE MOTOR CONTROLS Soft Starters Positive Displacement Pump Soft Starters

WWEPDASSRV12-150

General Product Specifications

- NEMA 4/12 Enclosure
- Service entrance rated
- 230/460V Rated
- Advanced Motor Protection
- Full panel surge protection
- CB with door mounted lockable handle
- Integral full rated bypass contactor with X-Line mode
- Accepts inputs for up to 7 Murphy switches
- Individually selectable for NO or NC
- Interposing relays isolation on Murphy inputs
- Vibration tip, crank case oil level, low pressure, high pressure, oil level, lubricator oil level, spare lamps
- Front panel indicators and keypad
- Start/stop, HOA, reset buttons
- Indicating LED's on I/O board (troubleshooting aid)
- Current imbalance, overcurrent, undercurrent, phase loss, shorted load, and ground fault protections standard

Rated Power			230V	75 HP
			460V	150 HP
Max Full Load Amps				210 A
Outside Dimensions				48x33x16
Input Voltage		230/460VAC ±10%, 50/60Hz Optional 380, 415, 575VAC		
Overload Rating		Normal Duty: 500% for 20s (Variable Torque Applications) Heavy Duty: 500% for 60s (Constant Torque Applications)		
Overload Range		160-240 A		
CT Rating		200:5		
Ambient Conditions		0° to 50 °C, 5-95% relative humidity, 0-3300ft above sea level (Can be designed to operate outside these conditions)		
Inputs	7	dry contacts using 24VDC		
Programmable Outputs	3	2-Form C (5A, 240VAC max) 1- Form A 26 programmable functions		
Dedicated Fault Output	1	AC Triac solid state switch 240VAC 50mA max		



