

WORLDWIDE MOTOR CONTROLS Soft Starters Heavy Duty Reduced Voltage Soft Starters With Full-Rated Wired Emergency Bypass

MODEL: WWEBCDSSRV12-125

General Product Specifications

- Full panel surge suppression
- Service entrance rated
- Integral full rated bypass contactor with X-Line mode
- Real-time thermal modeling and dynamic thermal register continuously calculates motor operating temperature even when your motor is not running
- Current imbalance, overcurrent, undercurrent, phase loss, shorted load, and ground fault protections standard
- PTC thermistor input for use on motors with embedded PTC temperature sensors
- Programmable overload trip curves
- Voltage Ramp
- \bullet Voltage Ramp with Current Limit
- Ramp times adjustable 1-120 seconds
- \bullet Current Ramp: CLT© Closed Loop Torque Ramp
- Current limit adjustable 200-600% of FLA
- \bullet 10-100% starting torque for 0.1-2 seconds

Rated Power		230V	60 HP	
Nateu rower			460V	125 HP
Max Full Load Amps				156 A
Outside Dimensions				48x33x16
I Innut Voltage I			208-480VAC ±10%, 50/60Hz Optional 380, 415, 575VAC	
Overload Rating		Normal Duty: 500% for 20s (Variable Torque Applications) Heavy Duty: 500% for 60s (Constant Torque Applications)		
Overload Range		120-180 A		
CT Rating		150:5		
Ambient Conditions		0° to 40 °C, 5-95% relative humidity, 0-3300ft above sea level (Can be designed to operate outside these conditions)		
Inputs	6	dry c	ontacts using	120VAC
Programmable Outputs	3	1- Fo	rm C (5A, 240 orm A ogrammable	·



