

WORLDWIDE MOTOR CONTROLS Soft Starters Positive Displacement Pump Soft Starters


WWEPDASSRV12-30


General Product Specifications

- NEMA 4/12 Enclosure
- Service entrance rated
- 230/460V Rated
- Advanced Motor Protection
- Full panel fused surge protection
- CB with door mounted lockable handle
- Integral full rated bypass contactor with X-Line mode
- Accepts inputs for up to 7 Murphy switches
- Individually selectable for NO or NC
- Interposing relays isolation on Murphy inputs
- Vibration tip, crank case oil level, low pressure, high pressure, oil level, lubricator oil level, spare lamps
- Front panel indicators and keypad
- Start/stop, HOA, reset buttons
- Indicating LED's on I/O board (troubleshooting aid)
- Current imbalance, overcurrent, undercurrent, phase loss, shorted load, and ground fault protections standard

| | | | | , |
|---------------------------|---|--|------|----------|
| Rated Power | | | 230V | 15 HP |
| | | | 460V | 30 HP |
| Max Full Load Amps | | | | 45 A |
| Outside Dimensions | | | | 37x15x12 |
| Input Voltage | | 230/460VAC ±10%, 50/60Hz Optional 380, 415, 575VAC | | |
| Overload Rating | | Normal Duty: 500% for 20s (Variable Torque Applications) Heavy Duty: 500% for 60s (Constant Torque Applications) | | |
| Overload Range | | 40-60 A | | |
| CT Rating | | 50:5 | | |
| Ambient Conditions | | 0° to 50 °C, 5-95% relative humidity, 0-3300ft above sea level (Can be designed to operate outside these conditions) | | |
| Inputs | 7 | dry contacts using 24VDC | | |
| Programmable Outputs | 3 | 2-Form C (5A, 240VAC max) 1- Form A 26 programmable functions | | |
| Dedicated Fault Output | 1 | AC Triac solid state switch 240VAC 50mA max | | |







TYPE: NEMA TYPE 4/12
COLOR: WHITE POWDER COAT
MATERIAL: 14 GA. [1.90MM] CRS
APPROXIMATE WEIGHT: 115 LBS. [55 KG]
DIMENSIONS: INCHES [MILLIMETERS]

WWEPDASSRV12-30

2.00 [50.80] APPROX.

9.12 [231.77] APPROX.

BOTTOM VIEW

