

Stearns Double C-Face Coupler Brakes

For standard NEMA C-Frame: 56C motor & quill input C-Flange

Suitable for Use with our full - line of Fractional hp Motors, including General Purpose, Stainless Steel, Permanent Magnet DC and Farm Duty Motors. The two standard stock parts eliminate the need for special designed brake motors for many applications.



Product Features

- Self-adjusting
- Solenoid actuated brake (SAB)
- Torque lb-ft: 1.5, 3, 6, 10
- IP54 protection
- Manual release knob
- AC operated coil Voltage: 115/230 (Vac 60 Hz), 230/460 (Vac 60 Hz)
- CSA Certified File LR6254
- RoHS3 compliant

Model Number	Description	Voltage
S - 105670205 QF	1.5 lb - ft, 56C, IP54	230/460
S - 105671205 QF	3 lb - ft, 56C, IP54	230/460
S - 105672205 QF	6 lb - ft, 56C, IP54	230/460
S - 105673205 QF	10 lb - ft, 56C, IP54	230/460
S - 105670205 PF	1.5 lb - ft, 56C, IP54	115/230
S - 105671205 PF	3 lb - ft, 56C, IP54	115/230
S - 105672205 PF	6 lb - ft, 56C, IP54	115/230
S - 105673205 PF	10 lb - ft, 56C, IP54	115/230

