# **Soft Starters** by Siemens

Compact and functional two and three-phase units

Worldwide Electric offers the Siemens 3RW family of compact soft starters. Each 3RW model allows for easy control of starting current and torque, tailored to your specific application needs. These starters provide power to the motor gradually and efficiently, enabling it to safely and reliably accelerate to full speed. As one of the leading technologies for simplified motor control in industrial applications.

#### **SIRIUS 3RW52**

- Three-phase operation
- -7.5 400 hp, 480 Vac

#### **SIRIUS 3RW50**

- Two-phase operation
- 100 400 hp, 480 Vac
- ATEX/IECEx certification

#### **SIRIUS 3RW40**

- Two-phase operation
- -7.5 75 hp, 480 Vac
- ATEX certification

Simple control and commissioning processes and extensive diagnostic capabilities make these soft starters an excellent choice for manufacturing managers, controls engineers, and maintenance engineers who are responsible for keeping operations running smoothly.

**Additional flexibility\*** is provided through optional HMI modules (display/keypad) and various communication options, including PROFINET, PROFIBUS, and Modbus TCP.



## **Features**

- Soft starting and stopping
- Current limiting
- Electronic/thermal motor overload protection
- Voltage ramp
- Minimum power loss and optimum motor control
- Efficient configuration with simple and fast commissioning using rotary dials (potentiometers)
- Soft torque operation
- Reduced mechanical loading and optimum pump stop
- Two-phase (3RW40 and 50) or three-phase (3RW52) units with a wide range for control supply and main Voltage.

### **Applications**

The 3RW soft starters offer a high degree of functionality in a compact design.

- Centrifugal pumps
- Ventilation fans
- Compressors (starting un-loaded)
- Conveyors
- Manufacturing/processing equipment, eg. saws, agitators

\*3RW50 and 52 models only





**Responsive**Service & Technical Support



**Quality Products** Competitive Pricing



**In Stock Availability**Warehouses Nationwide



**Fast Shipping** Same-Day Available



MC-FLY-3RW-02-2025

	200 V	230 V	480 V	Max FLA	Min OL Amps Inline	Model	Dimensions H x W x D (in)*	Weight (lbs)*
3RW52 Series   Three-	phase							
	2	3	7.5	11.5	5.5	3RW5213-1AC14	10.83 x 6.69 x 5.98	5.07
	3	5	10	15.9	7.5	3RW5214-1AC14	10.83 x 6.69 x 5.98	5.07
	5	7.5	15	22.3	11.5	3RW5215-1AC14	10.83 x 6.69 x 5.98	5.07
	7.5	10	20	28.4	14	3RW5216-1AC14	10.83 x 6.69 x 5.98	5.07
	10	10	20	33.5	15.5	3RW5217-1AC14	10.83 x 6.69 x 5.98	5.07
manifestal and a second and a s	10	10	30	41.6	20	3RW5224-1AC14	12.05 x 7.28 x 7.99	11.46
	15	20	40	55.5	25.5	3RW5225-1AC14	12.05 x 7.28 x 7.99	11.46
	20	25	50	68	32	3RW5226-1AC14	12.05 x 7.28 x 7.99	12.35
	25	30	60	82.5	40.5	3RW5227-1AC14	12.05 x 7.28 x 7.99	15.21
	30	30	75	101	53	3RW5234-6AC14	12.05 x 7.28 x 7.99	14.55
	40	40	100	128	68	3RW5235-6AC14	12.05 x 7.28 x 7.99	14.55
	50	50	100	153	81	3RW5236-6AC14	12.05 x 7.28 x 7.99	15.87
	60	60	150	186	90	3RW5243-6AC14	15.47 x 8.27 x 7.99	25.19
	60	75	150	220	100	3RW5244-6AC14	15.47 x 8.27 x 7.99	21.83
	75	100	200	279	135	3RW5245-6AC14	15.47 x 8.27 x 7.99	21.83
	100	125	250	328	160	3RW5246-6AC14	15.47 x 8.27 x 7.99	21.83
	150	150	350	416	200	3RW5247-6AC14	15.47 x 8.27 x 7.99	21.83
	150	200	400	504	240	3RW5248-6AC14	15.47 x 8.27 x 7.99	23.37
3RW50 Series   Two-phase								
	30	30	100	128	68	3RW5055-6AB14	4.72 x 7.80 x 9.80	8.81
	30	40	100	153	81	3RW5056-6AB14	4.72 x 7.80 x 9.80	8.81
	40	50	150	186	90	3RW5072-6AB14	6.30 x 9.06 x 11.10	17.64
	50	60	150	220	100	3RW5073-6AB14	6.30 x 9.06 x 11.10	18.01
	60	75	200	279	135	3RW5074-6AB14	6.30 x 9.06 x 11.10	18.01
	75	100	250	328	160	3RW5075-6AB14	6.30 x 9.06 x 11.10	18.30
	100	125	350	416	200	3RW5076-6AB14	6.30 x 9.06 x 11.10	18.30
	125	150	400	504	240	3RW5077-6AB14	6.30 x 9.06 x 11.10	18.51
3RW40 Series   Two-pl	hase							
	2	3	7.5	11	5	3RW4024-1BB14	1.78 x 4.92 x 6.06	1.60
	5	5	15	23	10	3RW4026-1BB14	1.78 x 4.92 x 6.06	1.60
	7.5	7.5	20	29	17	3RW4027-1BB14	1.78 x 4.92 x 6.06	1.60
	10	10	25	34	23	3RW4028-1BB14	1.78 x 4.92 x 6.06	1.60
	10	15	30	42	23	3RW4036-1BB14	2.17 x 5.67 x 6.70	2.82
	15	20	40	58	26	3RW4037-1BB14	2.17 x 5.67 x 6.70	2.82
	20	20	40	62	35	3RW4038-1BB14	2.17 x 5.67 x 6.70	2.83
	20	25	50	73	43	3RW4046-1BB14	2.76 x 6.30 x 7.40	4.09
* Given weights and dimensions are approximate	30	30	75	98	46	3RW4047-1BB14	2.76 x 6.30 x 7.40	4.09



