

DATA SHEET

Premium Efficiency Motor: **IOW7.5-9-256T**

60 Hz

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 7-Mar-2024
Document ID:

Customer:

MOTOR INFORMATION	
HP	7.5
RPM	900
Phase	3
Frequency	60 Hz
Voltage	230/460/796
Frame Size	256T
Enclosure	TEFC
Degree of Protection	IP55
Service Factor	1.15
Poles	8
Full Load Speed	844
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	H
Duty Cycle	S1 / Continuous
Slip	6.22%
NEMA Design	D
Moment of Inertia	1.94 lb.ft.^2
Locked Rotor Time (Hot)	6 seconds
Sound Pressure Level	76 dB(A)
Number of Starts	2 Cold / 1 Hot
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F2
Rotation	Bi-Directional
Area of Classification	Safe Area
Inverter Rating	No
Standard	NEMA MG-1
Approvals	CE

EFFICIENCY/POWER FACTOR		
LOAD	EFF	P. F.
100%	85.0 %	0.74
75%	86.2 %	0.66
50%	84.5 %	0.53

TORQUE		
FULL LOAD	LRT	BDT
46.7 lb.ft.	285 %	310 %

AMPERAGE INFORMATION			
	230V	460V	796V
Full Load Amps	22A	11A	6.4A
Locked Rotor Amps	117.4A	58.7A	33.9A
No Load Current	12.4A	6.2A	3.6A

BEARING INFORMATION	
DE Bearing	6309 C3
ODE Bearing	6309 C3
Grease Type	MOBIL POLYREX EM
DE Regreasing Interval	8500 Hours
ODE Regreasing Interval	8500 Hours
Grease Quantity DE/ODE	30g/30g

ADDITIONAL DATA	
F1 Suitable	Yes
Shaft Material	1045 Carbon Steel
Connection Diagram	230/460/796 V - 12 Lead ΔΔ/Δ/Y
Approximate Weight	251 lbs.


MOTOR DRAWING

Premium Efficiency Motor: **IOW7.5-9-256T**

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	J	P	O	T	AB
E	2F1	2F	H	BA										
5	8.25	10	0.53	4.25	12.36	11.57	24.84	6.25	0.787	2.362	12.6	12.89	2.05	10.5

SHAFT & KEY				
S	ES	R	N-W	U
0.375	2.91	1.416	4	1.625

TERMINAL BOX				
AA	XB	XC	XD	XF
1 1/2 NPT	3.05	7.41	6.3	9.17

PERFORMANCE CURVES

Premium Efficiency Motor:

IOW7.5-9-256T

WorldWide Electric Corporation


1 (800) 808-2131

Worldwideelectric.net



Document Generated: 7-Mar-2024	Customer:
Document ID:	

Motor Type	PEWWE					
Output Rating (HP)	7.5	FL Speed	844	796 volt FLA	6.4	A
Full Load Torque	46.7 lb.ft	LRT (%FLT)	285	460 volt FLA	11	A
Rotor Wk^2	1.94 lb-ft^2	BDT (%FLT)	310	230 volt FLA	22	A



NAMEPLATE / WIRING

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Premium Efficiency Motor:

IOW7.5-9-256T

Document Generated: 7-Mar-2024
Document ID:

Customer:

SAMPLE NAMEPLATE DATA

				OIL WELL PUMPING 3 PHASE INDUSTRIAL ELECTRIC MOTOR					
Model	<input type="text"/>	Ser No.	<input type="text"/>	TYPE	<input type="text"/>				
HP	<input type="text"/>	FR	<input type="text"/>	Encl	<input type="text"/>	IP	<input type="text"/>		
Voltage	<input type="text"/>	Hz	<input type="text"/>	Design	<input type="text"/>				
AMPS	<input type="text"/>	RPM	<input type="text"/>	Ins Cl	<input type="text"/>				
Rating	<input type="text"/>	°C Amb Cont	<input type="text"/>	S.F.	<input type="text"/>	kVA Code	<input type="text"/>		
Eff.	<input type="text"/>	%	Power Factor	<input type="text"/>					
DE Brng	<input type="text"/>	ODE Brng	<input type="text"/>						
Locked Rotor Torque/Rated Torque	<input type="text"/>		<input type="text"/>						
				Date	<input type="text"/>				
WorldWide Electric Corporation									

Model	<input type="text" value="IOW7.5-9-256T"/>						
HP	<input type="text" value="7.5"/>	Frame	<input type="text" value="256T"/>	Encl	<input type="text" value="TEFC"/>	IP	<input type="text" value="IP55"/>
Voltage	<input type="text" value="230/460/796"/>	Hz	<input type="text" value="60"/>	Design	<input type="text" value="D"/>		
Amps	<input type="text" value="22/11/6.4"/>	RPM	<input type="text" value="844"/>	Ins Cl	<input type="text" value="F"/>		
Rating	<input type="text" value="40°C Amb Cont"/>	S.F.	<input type="text" value="1.15"/>	kVA Code	<input type="text" value="H"/>		
Eff.	<input type="text" value="85.0%"/>	P.F.	<input type="text" value="0.74"/>				
DE Brng	<input type="text" value="6309 C3"/>	ODE Brng	<input type="text" value="6309 C3"/>				
Locked Rotor Torque/Rated Torque	<input type="text" value="285%"/>						