



# WORLDWIDE ELECTRIC MOTOR DATA SHEET

## OCCP1-18-143JM



HORSEPOWER	1		
RPM / POLES	1800 / 4		
VOLTAGE / PHASE	208 - 230 / 460 V / 3		
FRAME	143JM		
ENCLOSURE / DEGREE OF PROTECTION	ODP / IP23		
FREQUENCY	60 HZ Suitable For 50 HZ Operation With 1.0 SF		
FULL LOAD SPEED	1745 RPM		
SERVICE FACTOR	1.15 SF 60 HZ / 1.0 SF at 50 HZ		
INSULATION CLASS	F		
FULL LOAD AMPS; 230 / 460	2.6 / 1.3 A		
LOCKED ROTOR AMPS (STARTING); 230 / 460	21.46 / 10.73 A		
NO LOAD CURRENT	1.32 / 0.66 A		
NEMA CODE LETTER	K		
EFFICIENCY / POWER FACTOR	<u>LOAD</u>	<u>EFF.</u>	<u>P.F.</u>
	100%	85.5%	0.81
	75%	86.0%	0.75
	50%	84.2%	0.63
DUTY CYCLE	S1 / Continuous		
TORQUE	<u>FULL LOAD</u>	<u>LRT</u>	<u>BDT</u>
	3.03 lb.ft.	270.0%	333.0%
SLIP	3.07%		
NEMA DESIGN	B		
NUMBER OF STARTS (Hot / Cold)	2 Hot / 3 Cold		
MAX. AMBIENT TEMPERATURE	40° C		
MAX. ELEVATION	3300 Ft. Above Sea Level		
TEMPERATURE RISE (At Full Load)	80° C		
DE BEARING	6206ZZ		
ODE BEARING	6204ZZ		
GREASE TYPE	Multemp SRL		
MOUNTING	F1		
ROTATION	Bi-Directional		
APPROXIMATE WEIGHT	33.1 Lbs.		
AREA CLASSIFICATION	Non-Hazardous		
INVERTER RATING	10:1 CT / 20:1 VT PWM Type		
SPECIFICATION - In Accordance With	NEMA, UR		




JULY 16, 2020



# WORLDWIDE ELECTRIC MOTOR DRAWING

## OCCP-143JM



**DIMENSIONS - INCHES**

MOUNTING					A	B	C	D	G	AB	L	KEYSET	KEY	
E	2F1	2F2	H	BA								R	ES	S
2.75	4	5	0.34	2.75	6.5	6.5	14.57	3.5	0.118	5.384	6.73	0.771	1.65	0.188

FLANGE					AH	SHAFT EXTENSION								K
AK	AJ	BF	BB	BD		EL	EM	EP	EQ	ER	ET	EN	U	
4.5	5.875	3/8-16 * 0.56	0.156	6.63	7.313	1.156	1	1.16	0.625	4.25	2.875	3/8-16 * .075	.875	M5