



# WORLDWIDE ELECTRIC MOTOR DATA SHEET

## OCCP1.5-18-145JP



HORSEPOWER	1.5		
RPM / POLES	1800 / 4		
VOLTAGE / PHASE	208 - 230 / 460 V / 3		
FRAME	145JP		
ENCLOSURE / DEGREE OF PROTECTION	ODP/ IP23		
FREQUENCY	60 HZ Suitable For 50 HZ Operation With 1.0 SF		
FULL LOAD SPEED	1747 RPM		
SERVICE FACTOR	1.15 SF 60 HZ / 1.0 SF at 50 HZ		
INSULATION CLASS	F		
FULL LOAD AMPS; 230 / 460	4.2 / 2.1 A		
LOCKED ROTOR AMPS (STARTING); 230 / 460	34.52 / 17.26 A		
NO LOAD CURRENT	2.44 / 1.22 A		
NEMA CODE LETTER	L		
EFFICIENCY / POWER FACTOR	<u>LOAD</u>	<u>EFF.</u>	<u>P.F.</u>
	100%	86.5%	0.76
	75%	87.0%	0.68
	50%	85.1%	0.55
DUTY CYCLE	S1 / Continuous		
TORQUE	<u>FULL LOAD</u>	<u>LRT</u>	<u>BDT</u>
	3.03 lb.ft.	352.0%	373.0%
SLIP	2.959%		
NEMA DESIGN	B		
NUMBER OF STARTS (Hot / Cold)	2 Hot / 3 Cold		
MAX. AMBIENT TEMPERATURE	40° C		
MAX. ELEVATION	3300 Ft. Above Sea Level		
TEMPERATURE RISE (At Full Load)	80° C		
DE BEARING	6206ZZ		
ODE BEARING	6204ZZ		
GREASE TYPE	Multemp SRL		
MOUNTING	F1		
ROTATION	Bi-Directional		
APPROXIMATE WEIGHT	34.2 Lbs.		
AREA CLASSIFICATION	Non-Hazardous		
INVERTER RATING	10:1 CT / 20:1 VT PWM Type		
SPECIFICATION - In Accordance With	NEMA, UR		




JULY 16, 2020



# WORLDWIDE ELECTRIC MOTOR DRAWING

## OCCP-145JP



**DIMENSIONS - INCHES**

MOUNTING					A	B	C	D	G	AB	L	KEYSET	KEY	
E	2F1	2F2	H	BA								R	ES	S
2.75	4	5	0.34	2.75	6.5	6.5	17.63	3.5	0.118	5.384	6.73	0.771	1.65	0.188

FLANGE					AH	SHAFT EXTENSION								K
AK	AJ	BF	BB	BD		EL	EM	EP	EQ	ER	ET	EN	U	
4.5	5.875	3/8-16 * 0.56	0.156	6.63	7.313	1.156	1	1.16	1.563	7.31	5.938	3/8-16 * .075	.875	M5