

DATA SHEET

Premium Efficiency Motor: **ODPJ12-36-56CB**

60 Hz

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 5-May-2022
Document ID:

Customer:

MOTOR INFORMATION	
HP	1/2
RPM	3600
Phase	3
Frequency	60
Voltage	230/460
Frame Size	56C
Enclosure	ODP
Degree of Protection	IP23
Service Factor	1.60
Poles	2
Full Load Speed	3535
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	M
Duty Cycle	S1 / Continuous
Slip	1.86%
NEMA Design	B
Moment of Inertia	0.032146734375 lb.ft.^2
Locked Rotor Time (Hot)	12 seconds
Sound Pressure Level	78 dB(A)
Number of Starts/Hour (Hot)	2
Max Ambient Temperature	40°C
Max Elevation	3300 FASL
Mounting	F1
Rotation	Bi-Directional
Area of Classification	Safe
Inverter Rating	N/A
Standard	NEMA
Approvals	UL

EFFICIENCY/POWER FACTOR		
LOAD	EFF	P. F.
100%	73.4 %	0.68
75%	69.6 %	0.59
50%	62.2 %	0.48

TORQUE		
FULL LOAD	LRT	BDT
0.734 lb.ft.	298 %	381 %

AMPERAGE INFORMATION		
	230V	460V
Full Load Amps	1.86A	0.93A
Locked Rotor Amps	13.2A	6.6A
No Load Current	1.4284A	0.7142A
Usable at 208V	2.1 A	

BEARING INFORMATION	
DE Bearing	6203-ZZ
ODE Bearing	6203-ZZ
Grease Type	NS7 ENS
DE Regreasing Interval	-- Hours
ODE Regreasing Interval	-- Hours
Grease Quantity	--

ADDITIONAL DATA	
F2 Suitable	No
Shaft Material	S45C+SUS304
Connection Diagram	9 Lead Wye
Approximate Weight	21.6 lbs.

NAMEPLATE / WIRING

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Premium Efficiency Motor: **ODPJ12-36-56CB**

Document Generated: 5-May-2022
Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		OPEN DRIP PROOF THREE PHASE JET PUMP MOTOR						
ISO9001 CC306B		Encl : ODP		SN :			4 5 6 	
Model :	HP :	Poles : 2	FR :	Ins : F	IP 23	Max Amb 40°C	Duty : Cont	7 8 9 1 2 3 L1 L2 L3 208-230 V
Hz : 60	CODE :		Design :					4 5 6 7 8 9 1 2 3 L1 L2 L3 460 V
Volts :	P.F. :		DE BRG :					
Amps :	Eff :		ODE BRG :					
RPM :	S.F. :		WT : LBS					
Usable on 208V 60Hz network at ___ Amps		S.F.A :		Date :				
WorldWide Electric Corporation								

Model	ODPJ12-36-56CB	FR:	56C	Design:	B
HP:	1/2	CODE:	M	DE BRG:	6203-ZZ
Volts:	230/460V	P.F.:	0.68	ODE BRG:	6203-ZZ
Amps:	1.86/0.93A	Eff:	73.4%	WT:	21.6 lbs.
RPM:	3535	S.F.:	1.6		
		S.F.A:	1.208A		
Usable on 208V 60Hz Network at			2.1 A		