




F



|   |  |          |  |            |  |   |  |                       |  |                          |  |   |  |
|---|--|----------|--|------------|--|---|--|-----------------------|--|--------------------------|--|---|--|
| NO.   |  | PART NO. |  | MATERIAL   |  | PC  |  | RAW MATERIAL          |  | WEIGHT                   |  | NOTE  |  |
| <small>SCABBLE TOLERANCE</small><br>>0 ± 0.1<br>>6 ± 0.2<br>>30 ± 0.3<br>>120 ± 0.5<br>>315 ± 0.8 |  | DWG.     |  | 2020.07.01 |  | Y.S.P   |  | <div>WORLD WIDE</div> |  |                          |  |   |  |
|   |  | DESN.    |  | 2020.07.01 |  | Y.S.P   |  |                       |  |                          |  |   |  |
|   |  | APPR.    |  |            |  |   |  |                       |  |                          |  |   |  |
| <small>MACHINING REQUIRED</small><br>~ NO-MACHINING<br>▽ 50S<br>▽▽ 25S<br>▽▽▽ 6S                  |  |          |  | DATE       |  | NAME  |  | TITLE                 |  | KAN87-182/4TC+Power Lock |  |   |  |
| ANG. TOLERANCE±0.5  |  | SCALE    |  | 1:5        |  |  |  | DWG. NO.              |  | KAN87-A-POWER LOCK       |  | REV.  |  |
|   |  |          |  |            |  |   |  |                       |  |                          |  |  |  |